


# EYEZEN™+ 1, 2, & 3 CUTOUT CHART

Recommended Minimum Fitting Height 15mm



Please verify correct size with a ruler

## PRINTING INSTRUCTIONS

To print this measuring chart at the correct size from Acrobat Reader:

1. Go to **File**, then select **Print**
2. Under **Page Sizing & Handling** options, select **Actual Size**
3. Click on **Print** button to print

*Note: Chart measurements will be incorrect if "Fit" or other page-scaling options are selected. It is recommended to verify the printed chart is the correct size with a ruler.*

◇<sup>1</sup> Lens Engraving symbol location

| LENS ENGRAVING     |                |
|--------------------|----------------|
| PRODUCT            | SYMBOL         |
| Eyezen+ 1 (0.40 D) | ◇ <sup>1</sup> |
| Eyezen+ 2 (0.60 D) | ◇ <sup>1</sup> |
| Eyezen+ 3 (0.85 D) | ◇ <sup>1</sup> |

# BLOCKING AND FINISHING: EYEZEN™+ 1, 2, AND 3 LENSES

Eyezen™+ enhanced single vision lenses are an everyday single vision lens; however, they should be blocked and finished similarly to a progressive lens.

- FRP (Fitting Cross 4mm above the plane of the micro circles) should be used for **blocking for finishing**

Eyezen+ static cling verification decals (LEZN000021) are available from Essilor.

## VERIFICATION

### Instructions to verify power in Eyezen+ 1, 2, and 3 lenses

- 1 Verify the prescribed power at the distance verification circle
- 2 If prism was prescribed, then verify prism power at PRP
- 3 Confirm engraving to ensure the correct Eyezen+ 1, 2 or 3 was provided\*

\* Note: No other checks are necessary to confirm accommodative relief



Patients will not receive the full benefit of the accommodative relief in Eyezen+ 1, 2, or 3 if the Fitting Height is less than 15mm.

Go to [EyezenPro.com](http://EyezenPro.com) to find more resources and information on Eyezen+ lenses.

Eyezen™+